# Form-on

# smartPROP 20 sF2



Energy-saving due to low weight

Long service life thanks to galvanisation

Safe through anti-drop-out latch and crush guard

Top price-performance ratio







# Subject to change in the course of technical development

# Form-on smart**PROP** 20 sF2

## Your advantages:



Effortless and fast working thanks to its low weight.



Safe working thanks to anti-drop-out latch and crush guard.



Retaining its value thanks to highquality manufacturing and galvanisation.



Quick and safe release of the clamped floor prop through optimised thread pitch.

#### Form-on smart**PROP** 20 sF2

kN/length (cm) Length P.U. kg Art.no. 20 300 170 - 300 48 10.5 620005000 20 350 200 - 350 48 13.1 620006000

#### **TECHNICAL DATA**

**Load capacity:** 20 kN for each extension length with safety factor 2

Available: Standard lengths 3.0 m & 3.5 m

Туре	Extension length (mm)	Ø Breaking load (kN) of 5 tests	permissible load (kN) according safety factor 2	permissible load (kN) according to ANSI safety factor 3
300	3000	58.81	20.00	15.00
350	3500	55.19	20.00	15.00

#### **EXPERIMENTAL SETUP:**



NOTE: Cause of failure: Deformation of the punched hole.

### Not suitable for sale in Germany.

Prop length (m)	300	350
3.5		10.5
3.2		12.5
3.0	10.1	13.3
2.8	11.4	13.9
2.6	12.0	14.8
2.4	12.4	17.3
2.2	14.0	20.5
2.0	16.6	22.5
1.9	19.1	
1.7	21.4	

Permissible load capacity (kN) depending on the extension length of the upright tube. Calculated according to EN 1065.

